

TECHNICAL SPECIFICATIONS
DECORATIVE COATINGS
TECHNICAL DATA SHEET
NATIONAL TILE ADHESIVE

DESCRIPTION	A general purpose tile adhesive for fixing ceramic tile has been developed. It is based on synthetic polymer and has excellent adhesion to substrate, with good water resistance.
RECOMMENDED USE	For fixing ceramic tiles for external, internal walls and floorings.

TECHNICAL DATA

COLOURS	Off - White
APPEARANCE	Paste
ODOUR	Mild
SPECIFIC GRAVITY KG/L	1.50 ± 0.05
SPREADING RATE	Depends on the surface and thickness.
DRYING TIME @ 30°C	Temperature, humidity, air movement, film thickness and number of coats all affect the drying time.
	Touch dry (minutes) : 30
	Hard dry (hours) : 24
	Grouting (hours) : 24

APPLICATION DATA

APPLICATION METHOD	Trowel
THINNING (VOLUME)	Ready to use
THINNER / CLEANER	Water
APPLICATION PROCEDURE	Mix thoroughly and apply National Tile Adhesive on the substrate. Spread the adhesive uniformly on specific area, using trowel. Then fix and level the tile.
RECOMMENDED SYSTEM	- Surface should be clean and dry. - If required apply National PVA Sealer. - Then apply National Tile adhesive.

MISCELLANEOUS DATA

FLASH POINT	Water base
SHELF LIFE @ 30°C	18 months in original sealed containers, with proper storage conditions.

NOTE : We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details, refer specifier and safety data.