

Angle Drill LXT®

DDA351RFE

18V • 0 - 1 800 min⁻¹ • 10 mm

Angle drill with keyless chuck for tight spaces

An angle drill with an 89 mm head for access to tight spaces. With a max. torque of 13,5 Nm. The tool's chuck capacity is 1,5 – 10 mm. Two 3,0 Ah batteries and a rapid charger in a case.



TECHNICAL SPECIFICATIONS

| | |
|---|----------------------------|
| Nominal Battery Voltage | 18 V |
| Voltage LXT | ✓ |
| Battery protection | ✓ |
| No load speed | 0 - 1800 min ⁻¹ |
| Max. fastening torque Hard/Soft | - / 13,5 Nm |
| Max. Drilling Diameter in Wood | 25 mm |
| Max. Drilling Diameter in Steel | 10 mm |
| Driving Shank | 1/2"-20UNF " |
| Drill Chuck Capacity | 1,5 - 10 mm |
| Side Grip | ✓ |
| Sound Pressure Level (L _{pA}) | 70 dB(A) |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Vibration Level (3 axes), Drilling | ≤ 2,5 m/s ² |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Tool weight with battery (EPTA) | 1,6 - 1,9 kg |
| Product Dimensions (L x W x H): | 326 x 79 x 115 mm |
| Angle length | 88 mm |

USER BENEFITS

- LED light illuminates the work site

Link to Product page - www.makita.ae



RELATED PRODUCTS

STANDARD ACCESSORIES

153489-2

Grip complete 125 mm



STANDARD MACHINES

195584-2

Battery Charger LXT®, Li-ion, 14,4 -



OPTIONAL ACCESSORIES

153489-2

Grip complete 125 mm



821550-0

Маpак case (2)



OTHER

User manual

