Pencil Impact Driver

TD022DSJ

7.2V • 1/4" • 25 Nm • 0 – 2 450 min-1

Compact, high-speed impact driver

A compact, 7.2V pencil impact driver. An ideal tool for tight, awkward spaces, equipped with an LED light. Torque of 25 Nm. Two 1.5Ah batteries and a charger in a Makpac case.



TECHNICAL SPECIFICATIONS

Average Charging Time	35 min
Nominal Battery Voltage	7,2 V
No load speed	0 - 2450 min^{-1}
max fastening torgue impact drill	25 Nm
Tightening Capacity Standard Bolt	M3 - M8
Capacity machine screw	M3 - M8
Tightening Capacity High Tensile Bolt	M3 - M6
Impact	0 - 3000 min^{-1}
Sound Power Level (L_{WA})	96 dB(A)
Sound Pressure Level (L_{pA})	85 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	7,0 m/s^2
Vibration Uncertainty (K Factor)	1,5 m/s^2
Tool weight with battery (EPTA)	0,56 kg
Product Dimensions (L x W x H):	282 x 42 x 52 mm

USER BENEFITS

- LED light illuminates the work site

EAN 0088381833288

Link to Product page - www.makita.ae

RELATED PRODUCTS

STANDARD ACCESSORIES

821549-5
Makpac case (1)



STANDARD MACHINES

198000-3 (2x)
Battery Li-ion 7,2V / 1,5 Ah, BL0715



OPTIONAL ACCESSORIES

821549-5
Makpac case (1)



OTHER

User manual