

# Steel Rod Cutter LXT®

## DSC251ZK

18V • 10 - 25 mm • 2 200 min<sup>-1</sup>

**Fast, nearly spark-free cutting of steel rods and rebars**

A cutter designed for cutting steel rods and rebars. Max. cutting capacity of 25 mm, fine edge cutting (3,5 mm). A three-position removable side grip for added comfort. Tool only, battery and charger not included. Comes with case.



### TECHNICAL SPECIFICATIONS

Voltage LXT	✓
Brushless Motor	✓
Battery protection	✓
No load speed	2200 min <sup>-1</sup>
Blade	110 mm
Cutting Capacity Stainless Steel (up to 600N/mm <sup>2</sup> )	25 mm
Sound Pressure Level (L <sub>pA</sub> )	78 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s <sup>2</sup>
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Tool weight with battery (EPTA)	3,9 - 4,0 kg
Product Dimensions (L x W x H):	471 x 137 x 139 mm

### USER BENEFITS

- No dust, no sparks.
- Brushless maintenance-free and long-life motor

**EAN 0088381873543**

Link to Product page - [www.makita.ae](http://www.makita.ae)



# RELATED PRODUCTS

## STANDARD ACCESSORIES

153489-2  
Grip complete 125 mm



SC09003260  
Flangeless blade



## OPTIONAL ACCESSORIES

153489-2  
Grip complete 125 mm



SC09003260  
Flangeless blade



## OTHER

User manual

