



Impact Driver LXT®

DTS141Z

18V • 1/4" • 40 Nm • 0 – 3 200 min⁻¹

An oil-impulse driver with quiet operation and three power settings

An extremely quiet impact driver. Oil-impulse technology guarantees lower noise levels. A light and compact structure, thanks to a brushless engine and compact drive system. Tool only, battery and charger not included.



TECHNICAL SPECIFICATIONS

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery protection	✓
Brushless Motor	✓
No load speed	0 - 1200 / 2000 / 3200 min ⁻¹
max fastening torque impact drill	40 Nm
Tightening Capacity Standard Bolt	M5 - M8
Capacity machine screw	M4 - M8
Tightening Capacity High Tensile Bolt	M5 - M6
Impact	0 - 1400 / 2200 / 2700 min ⁻¹
Lenght of Blade	136 mm
Sound Pressure Level (L _{pA})	77 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Fastening Bolt	7,0 m/s ²

EAN 0088381684484

Link to Product page - www.makita.ae



RELATED PRODUCTS

OPTIONAL ACCESSORIES

195798-3

Battery Protector Cover (LXT 18 V)



821550-0

Makpac case (2)



OTHER

User manual

