



## **DEWALT D25721K-LX 7KG SDS MAX COMB. HAMMER 48MM 110V**

MODEL # D25721K-LX

- Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 48 mm in diameter. Core drilling up to 115 mm
- Active vibration control system incorporating a floating rear handle and damped side handle to reduce vibration
- Ergonomic; compact and slimline design maximizes control and offers easy access to confined spaces

### **FEATURES:**

- Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 48 mm in diameter. Core drilling up to 115 mm
- Active vibration control system incorporating a floating rear handle and damped side handle to reduce vibration
- Ergonomic; compact and slimline design maximizes control and offers easy access to confined spaces
- Electronic variable speed and impact energy control
- Lock-on switch for chipping
- Rotation-stop for demolition applications in brick; masonry and light chasing in concrete
- Brush wear and service indicators

## **SPECIFICATIONS:**

- Tool Holder SDS-Max  
Max. Drilling Capacity [Concrete] 48 mm
- Max. Drilling Capacity [Breakthrough bit] 80 mm
- Max. Drilling Capacity [Core bit] 115 mm
- Power Input 1350 Watts
- Power Output 840 Watt
- Impact energy (EPTA 05/2009) 11 J
- Load Speed 132-265 rpm
- Blows per Minute 1225-2450 bpm
- Length 528 mm
- Height 268 mm
- Width 116 mm
- Weight 8.7 kg
- Hand/Arm Vibration – Hammer drilling into concrete 8.9 m/s<sup>2</sup>
- Uncertainty K 1 (Vibration) 1.5 m/s<sup>2</sup>
- Hand/Arm Vibration – Chiseling 8.1 m/s<sup>2</sup>
- Uncertainty K 2 (Vibration) 1.5 m/s<sup>2</sup>
- Sound Pressure 96 dB(A)
- Sound Pressure Uncertainty 3 dB(A)
- Sound Power 107 dB(A)
- Sound Power Uncertainty 3 dB(A)

## **INCLUDED:**

- Kit Box
- 2 Position Side Handle
- User Guide